

# **TITAN-550**





**Convenience Stores / Small Grocery Stores** 





Tobacco Stores / Liquor Stores





Apparel Stores / Salons





 Table Service and Quick Service Restaurants



Powerful POS Terminal with True Flat Touch Screen



The TITAN's i3 3.3GHz processor brings traditional desktop computing power to a POS terminal designed for the rigors of retail life. It easily supports the most demanding software applications and is ideally suited to be used as a workstation or a server in multi-terminal installations.

- Intel Core i3 3.3GHz Processor
- 5-Wire Resistive Touch
- · Performance and Reliability
- Vivid LED Backlight for Reliability and Energy Savings
- True-Flat Debris Will Not Collect and Disrupt Touch Operation – Resists Liquid Splashes and Allows Easy Clean Up
- Integrated Power Supply



Hardware, Paint or General Retail Stores

## TITAN-550 Touch Screen Terminal



Sleek Cabinet Design

### **Options and Upgrades**

Configure your system with these easy to add options:

- Integrated VFD Customer Display
- 2 Lines x 20 Characters
- Integrated 15", 9.7" or 7" LCD Customer Displays
- Integrated Fingerprint Reader
- Solid State Drive
- SATA Compact Flash Adaptor
- · WiFi Module
- Wall Mount Bracket with Standard VESA Configuration

### Applications

The attractive, powerful TITAN-550 is ideal for demanding applications including table service, retail scanning and many more like these:

- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks

#### Connectivity A Line-Out

**B** CFast Slot C Parallel D DC Out (For Rear K COM4 (Powered) LCD) E COM1 (Powered) M Cash Drawer F VGA **G** LAN

- Kitchen Video
- Medical
- Message Stations
- Point of Sale Quick Service
- Restaurant
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video Table Service
- Restaurant
- Training
- Unattended
- Workstations
- **H** USB (2) I COM2 (Powered) J COM3 (Powered) L USB (2) N DC In (Power) O Hard Disk Drive



**Optional Integrated 9.7" Rear** LCD Customer Display

Specifications



**Optional Integrated Rear** VFD Customer Display



Integrated Power Supply and Cable Management Keeps Cords Hidden and Organized

Specifica	alions			
Processor:		Intel Core i3 3.3GHz		
Cores / Threads:		Dual Core / 4 Threads		
Cache Memory:		3MB		
Bus Speed:		5 GT/s (Giga Transfers per Second)		
Display LCD:		True Flat 15" LCD with LED Backlighting		
Resolution:		1024 x 768		
Brightness:		Adjustable Up to 350 cd/m2		
Integrated Speakers:		Integrated 2 Watt Speakers		
Chipset (PCH):		H61		
Touch –	Panel:	5-Wire Resistive Touch		
ioucii –		Over 36 Million Touches		
MOD.	Reliability:			
MCR:		Integrated USB Interface Triple Track MCR		
Hard Drive:		320GB 2.5" With SATA Interface		
RAM Memory:		2GB SODIMM DDR3 (1600MHz) Exp. To 16GB (2 Slots)		
Video Memory:		Shared System Memory Up to 1.7GB (Windows 7)		
Compact Flash:		Optional SATA Adaptor		
Serial Ports:		COM1, COM2, COM4 = DB9M With Pin 9 Voltage		
		(0V/+5V/+12V) Selectable By BIOS / COM3 = RJ45 Pin 1		
		Voltage (0V+5V/+12V) Selectable By Jumper		
		COM4 = RJ45 for Customer VFD		
Parallel Port:		One DB25F		
USB Ports:		6 V2.0 (2 Left Side / 4 Top)		
Cash Drawer Port:		RJ11, 12V or 24V Selectable By Bios		
		(Maximum 2 Drawers – Supports Open/Close)		
Keyboard / Mouse Port:		Not Applicable (Use USB Port)		
LAN Port:		RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111DL		
VGA Port:		One DB15F Display Port For Second LCD		
		(Maximum Resolution 2048 x 1536)		
Audio Port:		One Line-Out		
Mic Port:		One Mic-In		
Power Supply:		150W, 19V/7.9A Int. Power Adaptor 100-240V 50-60Hz		
Current / Power Usage:		0.4A / 45W (110V Idle Environment)		
		$32^{\circ}$ F to $95^{\circ}$ F ( $0^{\circ}$ C to $35^{\circ}$ C)		
Operating Temperature:				
Compatible O/S:		POSReady 2009 / POSReady 7 / Windows Pro 7 /		
		Windows Pro 8 / Windows 8 Industry Pro Windows 10 Retail / Windows 10 Pro		
Dimension (194				
Dimen. / We	eight – Base:	8-3/4"W x 2-3/8"H x 9-9/16"D		
	Overall:	12-1/2"W x 15"H x 9-9/16"D	18.56 lbs.	
	pping Carton:	17"W x 12-1/2"H x 19"D	20.02 lbs	
Safety and	EMI:	FCC, RoHS	_ ,	
A B	E	GIK O	Two USB	
	1		Ports on	
í 庄 🚣			the Left Side	
CFAST SLOT	- () - COM1			
o			Optional	
LINE OUT L <sup>9</sup> T	DC-0UT V 6A (12 V)	USB COM3 USB DRAMER	Fingerprint	
Ċ	ĎĖ	Ĥ Ĵ Ĺ M Ń	Reader	
rvice marks or registered trademarks of their respective owners.				
without notice. © 2015, Printed in U.S.A. Lit-253				

All product and company names are trademarks, se All features and specifications are subject to change without notice. © 2015. Printed in U.S.A.

Lit-253